

超快恢复二极管

Ultra Fast Recovery Diodes $T_j = -40^{\circ}\text{C} \sim +125^{\circ}\text{C}$, $T_{jm} = +125^{\circ}\text{C}$

型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V _{RRM}	I _{FAV}	I _{FSM}	I _R at V _R =V _{RRM}		V _{Fmax} at I _F		trr (max)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
MUR820	200	8	100	2	1	1	8	30	TO-220AC	1	
MUR860	600	8	100	2	2	2	8	50	TO-220AC	1	
MUR860F	600	8	100	2	2	2	8	50	TO-220F-2L	1	
MUR860S	600	8	100	2	2	2	8	50	TO-263	1	
MUR1020CT	200	10	100	2	1	1	5	30	TO-220AB	2	
MUR1040	400	10	100	3	1	1	10	35	TO-220AC	1	
MUR1060CT	600	10	100	3	1	2	5	50	TO-220AB	2	
MUR1060CTF	600	10	100	3	1	2	5	50	TO-220F-3L	2	
MUR1520	200	15	100	5	3	1	15	30	TO-220AC	1	
MUR1540	400	15	100	5	3	1	15	35	TO-220AC	1	
MUR1560	600	15	100	5	3	2	15	50	TO-220AC	1	
MUR1560F	600	15	100	5	3	2	15	50	TO-220F-2L	1	
MUR1560S	600	15	100	5	3	2	15	50	TO-263	1	
MUR1620CT	200	16	150	5	10	1	8	30	TO-220AB	2	
MUR1620AT	200	16	150	5	10	1	8	30	TO-220AB	3	
MUR1640CT	400	16	140	5	10	1	8	35	TO-220AB	2	
MUR1640AT	400	16	140	5	10	1	8	35	TO-220AB	3	
MUR1640DT	400	15	140	5	10	1	8	35	TO-220AB	4	
MUR1660CT	600	16	125	5	10	2	8	50	TO-220AB	2	
MUR1660AT	600	16	125	5	10	2	8	50	TO-220AB	3	
MUR1660DT	600	16	125	5	10	2	8	50	TO-220AB	4	
MUR2020CT	200	20	160	10	10	1	10	30	TO-220AB	2	
MUR2020AT	200	20	160	10	10	1	10	30	TO-220AB	3	
MUR2020DT	200	20	160	10	10	1	10	30	TO-220AB	4	
MUR2040CT	400	20	150	20	10	1	10	35	TO-220AB	2	
MUR2040AT	400	20	150	20	10	1	10	35	TO-220AB	3	
MUR2040DT	400	20	150	20	10	1	10	35	TO-220AB	4	
MUR2060CT	600	20	110	50	1	2	10	50	TO-220AB	2	
MUR2060AT	600	20	110	50	1	2	10	50	TO-220AB	3	
MUR2060DT	600	20	110	50	1	2	10	50	TO-220AB	4	
MUR2960	600	30	250	100	7	2	30	50	TO-220AC	1	
MUR2960F	600	30	250	100	7	2	30	50	TO-220F-2L	1	
MUR2960S	600	29	250	100	7	2	30	50	TO-263	1	
MUR3020CT	200	30	250	5	1	1	15	35	TO-220AB	2	
MUR3020	200	30	300	250	1	1	30	35	TO-247AC	1	
MUR3020PT	200	30	150	50	3	1	15	35	TO-247AD	2	
MUR3030	300	30	300	100	1	1	30	35	TO-247AC	1	
MUR3030PT	300	30	150	50	3	1	15	35	TO-247AD	2	
MUR3040	400	30	300	100	7	2	30	50	TO-247AC	1	
MUR3040PT	400	30	150	50	3	2	15	50	TO-247AD	2	
MUR3060	600	30	300	100	7	2	30	50	TO-247AC	1	
MUR3060PT	600	30	150	50	3	2	15	50	TO-247AD	2	
MUR6020	200	60	600	50	11	1	60	35	TO-247AC	1	
MUR6020PT	200	60	325	200	5	1	30	50	TO-247AD	2	
MUR6030	300	60	550	200	14	1	60	35	TO-247AC	1	
MUR6030PT	300	60	325	200	5	1	30	50	TO-247AD	2	
MUR6040	400	60	550	500	14	2	60	50	TO-247AC	1	
MUR6040PT	400	60	300	100	7	2	30	50	TO-247AD	2	
MUR6060	600	60	550	200	14	2	60	50	TO-247AC	1	
MUR6060PT	600	60	300	100	7	2	30	50	TO-247AD	2	
MUR12060	600	120	600	3mA	20	2	120	75	TO-247AC	1	

Алматы (7273)495-231
 Ангарск (3955)60-70-56
 Архангельск (8182)63-90-72
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Благовещенск (4162)22-76-07
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Владикавказ (8672)28-90-48
 Владимир (4922)49-43-18
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
 Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Коломна (4966)23-41-49
 Кострома (4942)77-07-48
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Курган (3522)50-90-47
 Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Ноябрьск (3496)41-32-12
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Петрозаводск (8142)55-98-37
 Псков (8112)59-10-37
 Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Саранск (8342)22-96-24
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Сургут (3462)77-98-35
 Сыктывкар (8212)25-95-17
 Тамбов (4752)50-40-97
 Тверь (4822)63-31-35

Киргизия +996(312)96-26-47





Тольятти (8482)63-91-07
 Томск (3822)98-41-53
 Тула (4872)33-79-87
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Улан-Удэ (3012)59-97-51
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Чебоксары (8352)28-53-07
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Чита (3022)38-34-83
 Якутск (4112)23-90-97
 Ярославль (4852)69-52-93

<https://sirectifier.nt-rt.ru/> || sfx@nt-rt.ru

软恢复特性高性能高结温超快恢复外延二极管

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes

Tj = -55°C ~ +175°C, Tjm = +175°C


型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V _{RRM}	I _{FAV}	I _{FSM}	I _{RRM} at V _R =V _{RRM}		V _{Fmax} at I _{FM}		trr (typ)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
HUR820	200	8	96	10	0.1	1.000	8	25	TO-220AC	1	 TO-220F-2L
HUR1020	200	10	150	10	0.1	1.000	10	25	TO-220AC	1	
HUR1520	200	15	220	10	0.1	1.000	15	25	TO-220AC	1	 TO-220AC
HUR1520F	200	15	220	10	0.1	1.000	15	25	TO-220F-2L	1	
HUR2020	200	20	250	20	0.2	1.000	20	25	TO-220AC	1	 TO-220AB
HUR2520	200	25	300	20	0.2	1.000	25	25	TO-220AC	1	
HUR3020	200	30	360	30	0.3	1.000	30	25	TO-247AC	1	 TO-220F-3L
HUR4020	200	40	480	30	0.3	1.000	40	25	TO-247AC	1	
HUR5020	200	50	600	50	0.5	1.000	50	25	TO-247AC	1	 TO-247AC
HUR6020	200	60	720	50	0.5	1.000	60	25	TO-247AC	1	
HUR2020CTA1	200	2X10	150	10	0.1	1.000	10	25	TO-220F-3L	2	 TO-264
HUR2020CTA2	200	2X10	150	10	0.1	1.000	10	25	TO-220AB	2	
D20LC20UB4	200	2X10	150	10	0.1	1.000	10	25	TO-3PF	2	 TO-247AD
D20LC20UA6	200	2X10	150	10	0.1	1.000	10	25	TO-263	2	
HUR3020PT	200	2X15	220	20	0.2	1.000	15	25	TO-247AD	2	 TO-264
HUR4020PT	200	2X20	250	20	0.2	1.000	20	25	TO-247AD	2	
HUR5020PT	200	2X25	300	20	0.2	1.000	25	25	TO-247AD	2	内部电路Circuit
HUR6020PT	200	2X30	360	30	0.3	1.000	30	25	TO-247AD	2	
HUR7020PT	200	2X35	400	30	0.3	1.000	35	25	TO-247AD	2	 Circuit 1
HUR8020PT	200	2X40	480	30	0.3	1.000	40	25	TO-247AD	2	
HUR1040	400	10	105	10	0.1	1.300	10	35	TO-220AC	1	 Circuit 2
HUR1540	400	15	160	10	0.1	1.300	15	35	TO-220AC	1	
HUR2040	400	20	210	20	0.2	1.300	20	35	TO-220AC	1	
HUR3040	400	30	320	30	0.3	1.300	30	35	TO-247AC	1	
HUR4040	400	40	420	30	0.3	1.300	40	35	TO-247AC	1	
HUR6040	400	60	630	50	0.5	1.300	60	35	TO-247AC	1	
HUR8040	400	80	840	60	0.6	1.300	80	35	TO-247AC	1	
HUR10040	400	100	950	70	0.7	1.300	100	35	TO-247AC	1	
HUR2040CTA1	400	2X10	105	10	0.1	1.300	10	35	TO-220F-3L	2	
HUR2040CTA2	400	2X10	105	10	0.1	1.300	10	35	TO-220AB	2	
HUR3040PT	400	2X15	160	10	0.1	1.300	15	35	TO-247AD	2	
HUR4040PT	400	2X20	210	20	0.2	1.300	20	35	TO-247AD	2	
HUR6040PT	400	2X30	320	30	0.3	1.300	30	35	TO-247AD	2	
HUR8040PT	400	2X40	420	30	0.3	1.300	40	35	TO-247AD	2	
HUR12040PT	400	2X60	630	50	0.5	1.300	60	35	TO-264	2	
HUR1560	600	15	140	10	0.1	1.550	15	40	TO-220AC	1	
HUR1560F	600	15	140	10	0.1	1.550	15	40	TO-220F-2L	1	
HUR2060	600	20	190	20	0.2	1.550	20	40	TO-220AC	1	
HUR3060	600	30	285	30	0.3	1.550	30	40	TO-247AC	1	
HUR4060	600	40	380	30	0.3	1.550	40	40	TO-247AC	1	
HUR6060	600	60	570	50	0.5	1.550	60	40	TO-247AC	1	
HUR7560	600	75	710	60	0.6	1.550	75	40	TO-247AC	1	
HUR10060	600	100	950	70	0.7	1.550	100	40	TO-247AC	1	
HUR12060	600	120	1140	80	0.8	1.550	120	40	TO-247AC	1	
HUR15060	600	150	1425	100	1	1.550	150	40	TO-247AC	1	
HUR2060CTA1	600	2X10	95	10	0.1	1.550	10	40	TO-220F-3L	2	
HUR2060CTA2	600	2X10	95	10	0.1	1.550	10	40	TO-220AB	2	
HUR3060PT	600	2X15	140	10	0.1	1.550	15	40	TO-247AD	2	
HUR4060PT	600	2X20	190	20	0.2	1.550	20	40	TO-247AD	2	

型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V _{RRM}	I _{FAV}	I _{FSM}	I _{RRM} at V _R =V _{RRM}		V _{Fmax} at I _{FM}		trr (typ)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
HUR6060PT	600	2X30	285	30	0.3	1.550	30	40	TO-247AD	2	TO-220F-2L
HUR8060PT	600	2X40	380	30	0.3	1.550	40	40	TO-247AD	2	
HUR12060PT	600	2X60	570	50	0.5	1.550	60	40	TO-264	2	TO-220AC
HUR15120	1200	15	120	10	0.1	2.000	15	50	TO-220AC	1	
HUR15120F	1200	15	120	10	0.1	2.000	15	50	TO-220F-2L	1	TO-220AB
HUR20120	1200	20	160	20	0.2	2.000	20	50	TO-220AC	1	
HUR20120F	1200	20	160	20	0.2	2.000	20	50	TO-220F-2L	1	TO-220F-3L
HUR30120	1200	30	240	30	0.3	2.000	30	50	TO-247AC	1	
HUR40120	1200	40	320	30	0.3	2.000	40	50	TO-247AC	1	TO-247AC
HUR606120	1200	60	480	50	0.5	2.000	60	50	TO-247AC	1	
HUR75120	1200	75	600	60	0.6	2.000	75	50	TO-247AC	1	TO-264
HUR100120	1200	100	800	70	0.7	2.000	100	50	TO-247AC	1	
HUR120120	1200	120	960	80	0.8	2.000	120	50	TO-247AC	1	SOT-227
HUR150120	1200	150	1200	100	1	2.000	150	50	TO-247AC	1	
HUR20120CTA1	1200	2X10	80	10	0.1	2.000	10	50	TO-220F-3L	2	TO-247AD
HUR20120CTA2	1200	2X10	80	10	0.1	2.000	10	50	TO-220AB	2	
HUR30120PT	1200	2X15	120	10	0.1	2.000	15	50	TO-247AD	2	TO-264
HUR40120PT	1200	2X20	160	20	0.2	2.000	20	50	TO-247AD	2	
HUR60120PT	1200	2X30	240	30	0.3	2.000	30	50	TO-247AD	2	SOT-227
HUR80120PT	1200	2X40	320	30	0.3	2.000	40	50	TO-247AD	2	
HUR120120PT	1200	2X60	480	50	0.5	2.000	60	50	TO-264	2	TO-247AD
HUR150120PT	1200	2X75	600	60	0.6	2.000	75	50	TO-264	2	
HUR2×30-20	200	2×30	360	250	1	1.10	30	25	SOT-227	3	TO-264
HUR2×30-30	300	2×30	300	250	1	1.15	30	30	SOT-227	3	
HUR2×30-40	400	2×30	300	250	1	1.30	30	35	SOT-227	3	SOT-227
HUR2×30-60	600	2×30	250	250	1	1.55	30	40	SOT-227	3	
HUR2×30-120	1200	2×30	200	250	1	2.00	30	50	SOT-227	3	TO-247AD
HUR2×60-20	200	2×60	600	650	2.5	1.10	60	25	SOT-227	3	
HUR2×60-30	300	2×60	600	650	2.5	1.15	60	30	SOT-227	3	TO-264
HUR2×60-40	400	2×60	600	650	2.5	1.30	60	35	SOT-227	3	
HUR2×60-60	600	2×60	600	650	2.5	1.55	60	40	SOT-227	3	SOT-227
HUR2×60-120	1200	2×60	500	1000	4	2.00	60	50	SOT-227	3	
HUR2×100-40	400	2×100	1000	1000	4	1.45	100	35	SOT-227	3	TO-247AD
HUR2×100-60	600	2×100	1000	1000	4	1.54	100	40	SOT-227	3	
HUR2×100-120	1200	2×100	950	1000	5	2.00	100	50	SOT-227	3	TO-264
HUR2×120-20	200	2×120	1100	1000	4	1.15	100	30	SOT-227	3	
HUR2×120-40	400	2×120	1050	1000	4	1.35	100	35	SOT-227	3	SOT-227
HUR2×140-20	200	2×140	1000	1000	4	1.15	100	30	SOT-227	3	
HUR2×140-40	400	2×140	1000	1000	4	1.50	100	35	SOT-227	3	


内部电路 Circuits



Circuit 1



Circuit 2








Circuit 3









软恢复特性超快恢复外延二极管模块


Soft Recovery Behaviour Ultra Fast Recovery Epitaxial Diode Modules

Tj = -40°C ~ +125°C, Tjm = +125°C


E310749

型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V _{RRM}	I _{FAV}	I _{FSM}	I _{RRM} at V _R =V _{RRM}		V _{Fmax} at I _{FM}		trr (typ)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
S1PDBF26N06E1	600	26	110	100	0.50	1.60	15	35	E1	4	E1 
S1PDBF55N12E1	1200	55	200	250	1.00	2.00	30	50	E1	4	
S1PDBF100N12E2	1200	100	500	1000	2.50	2.00	50	50	E2	5	
S3PDBF56N06E1	600	56	110	100	0.50	1.60	20	35	E1	4	
S3PDBF75N12E1	1200	75	200	250	1.00	2.00	30	50	E1	4	
SDKF2X60-17B1	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	6	E2 
SDKF2X60-17B2	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	7	
SDAF2X60-17B1	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	8	
SDAF2X60-17B2	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	9	
SDEF2X60-17B1	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	10	
SDEF2X60-17B2	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	11	Fig.2 
SDF2X60-17B1	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	12	
SDF2X60-17B2	1700	2X60	1000	400	4.00	2.50	60	150	Fig.2	13	
SDKF2×75-12B1	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	6	
SDKF2×75-12B2	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	7	
SDAF2×75-12B1	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	8	
SDAF2×75-12B2	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	9	
SDEF2×75-12B1	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	10	
SDEF2×75-12B2	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	11	
SDF2×75-12B1	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	12	Circuit 4 
SDF2×75-12B2	1200	2×75	1200	500	10.00	2.17	75	60	Fig.2	13	
SDKF2×100-04B1	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	6	
SDKF2×100-04B2	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	7	
SDAF2×100-04B1	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	8	
SDAF2×100-04B2	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	9	Circuit 5 
SDEF2×100-04B1	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	10	
SDEF2×100-04B2	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	11	
SDF2×100-04B1	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	12	
SDF2×100-04B2	400	2×100	2000	500	10.00	1.30	100	50	Fig.2	13	
SDKF2×100-06B1	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	6	Circuit 6 (SDKF-B1) 
SDKF2×100-06B2	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	7	
SDAF2×100-06B1	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	8	
SDAF2×100-06B2	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	9	
SDEF2×100-06B1	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	10	
SDEF2×100-06B2	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	11	Circuit 7 (SDKF-B2) 
SDF2×100-06B1	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	12	
SDF2×100-06B2	600	2×100	2000	500	10.00	1.35	100	50	Fig.2	13	
SDAF2X100-07D5	700	2X100	2000	500	10.00	1.60	100	50	Fig.60	9	
SDKF2X100-07D5	700	2X100	2000	500	10.00	1.60	100	50	Fig.60	7	
SDKF2×100-12B1	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	6	Circuit 8 (SDAF-B1) 
SDKF2×100-12B2	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	7	
SDAF2×100-12B1	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	8	
SDAF2×100-12B2	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	9	
SDEF2×100-12B1	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	10	
SDEF2×100-12B2	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	11	Fig.3 
SDF2×100-12B1	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	12	
SDF2×100-12B2	1200	2×100	2500	500	15.00	2.00	100	60	Fig.2	13	
SDKF2×150-04B1	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	6	
SDKF2×150-04B2	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	7	

型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V_{RRM}	I_{FAV}	I_{FSM}	I_{RRM} at $V_R=V_{RRM}$		V_{Fmax} at I_{FM}		t_{rr} (typ)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
SDAF2×150-04B1	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	8	
SDAF2×150-04B2	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	9	
SDEF2×150-04B1	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	10	
SDEF2×150-04B2	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	11	
SDFF2×150-04B1	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	12	
SDFF2×150-04B2	400	2×150	3040	600	18.00	1.55	150	50	Fig.3	13	
SDKF2×150-06B1	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	6	
SDKF2×150-06B2	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	7	
SDAF2×150-06B1	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	8	
SDAF2×150-06B2	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	9	
SDEF2×150-06B1	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	10	
SDEF2×150-06B2	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	11	
SDFF2×150-06B1	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	12	Circuit 9 (SDAF-B2) 
SDFF2×150-06B2	600	2×150	3040	600	18.00	1.55	150	50	Fig.3	13	
SDKF2×200-04B1	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	6	
SDKF2×200-04B2	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	7	Circuit 10 (SDEF-B1) 
SDAF2×200-04B1	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	8	
SDAF2×200-04B2	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	9	
SDEF2×200-04B1	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	10	Circuit 11 (SDEF-B2) 
SDEF2×200-04B2	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	11	
SDFF2×200-04B1	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	12	
SDFF2×200-04B2	400	2×200	3300	600	18.00	1.55	200	50	Fig.3	13	Circuit 12 (SDFF-B1) 
SDKF2×200-06B1	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	6	
SDKF2×200-06B2	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	7	
SDAF2×200-06B1	600	2×200	2100	600	18.00	1.55	200	50	Fig.3	8	Circuit 13 (SDFF-B2) 
SDAF2×200-06B2	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	9	
SDEF2×200-06B1	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	10	
SDEF2×200-06B2	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	11	Circuit 14 (SDEF-DA) 
SDFF2×200-06B1	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	12	
SDFF2×200-06B2	600	2×200	3300	600	18.00	1.55	200	50	Fig.3	13	
SDKF2×200-12B1	1200	2×200	3300	600	18.00	1.55	200	50	Fig.3	6	Circuit 15 (SDF-B) 
SDKF2×200-12B2	1200	2×200	3300	600	18.00	1.55	200	50	Fig.3	7	
SDAF2×200-12B1	1200	2×200	3300	600	18.00	1.55	200	50	Fig.3	8	
SDAF2×200-12B2	1200	2×200	3300	600	18	1.55	200	50	Fig.3	9	
SDEF2×200-12B1	1200	2×200	3300	600	18	1.55	200	50	Fig.3	10	
SDEF2×200-12B2	1200	2×200	3300	600	18	1.55	200	50	Fig.3	11	
SDFF2×200-12B1	1200	2×200	3300	600	18	1.55	200	50	Fig.3	12	
SDFF2×200-12B2	1200	2×200	3300	600	18	1.55	200	50	Fig.3	13	
SDEF2X250-12DA	1200	2X250	3800	700	18	2.00	250	50	Fig.34	14	
SDKF2×300-06B1	600	2×300	4400	800	20	1.55	300	50	Fig.3	6	
SDKF2×300-06B2	600	2×300	4400	800	20	1.55	300	50	Fig.3	7	
SDAF2×300-06B1	600	2×300	4400	800	20	1.55	300	50	Fig.3	8	
SDAF2×300-06B2	600	2×300	4400	800	20	1.55	300	50	Fig.3	9	
SDEF2×300-06B1	600	2×300	4400	800	20	1.55	300	50	Fig.3	10	
SDEF2×300-06B2	600	2×300	4400	800	20	1.55	300	50	Fig.3	11	
SDFF2×300-06B1	600	2×300	4400	800	20	1.55	300	50	Fig.3	12	
SDFF2×300-06B2	600	2×300	4400	800	20	1.55	300	50	Fig.3	13	
SDKF2×350-02B1	200	2×350	5400	1000	30	1.20	350	35	Fig.3	6	
SDKF2×350-02B2	200	2×350	5400	1000	30	1.20	350	35	Fig.3	7	
SDF120-17B	1700	120	2000	6000	80	2.20	120	90	Fig.4	15	
SDF200-12B	1200	200	2550	3000	10	1.80	200	50	Fig.4	15	
SDF200-17B	1700	200	2200	3200	15	2.20	200	90	Fig.4	15	

型号 TYPE	电气特性Electrical Characteristics								封装外形 Package Style	内部电路 Circuits	外形图 Outlines
	V _{RRM}	I _{FAV}	I _{FSM}	I _{RRM} at V _R =V _{RRM}		V _{Fmax} at I _{FM}		trr (typ)			
				25°C	125°C	V	A				
	V	A	A	μA	mA	V	A	ns			
SDF300-05D4	500	300	4100	500	30	1.10	300	85	Fig.53 (D4)	16	
SDF300-06D4	600	300	4000	500	30	1.30	300	75	Fig.53 (D4)	16	
SDF300-07D4	700	300	4000	500	30	1.50	300	75	Fig.53 (D4)	16	
SDF450-12	1200	453	4800	2000	50	2.00	450	60	Fig.4	15	
SDF500-06	600	514	5280	1500	50	1.60	500	50	Fig.4	15	
SDF550-02	200	550	5580	1500	50	1.25	550	35	Fig.4	15	
SUR150-02NB	200	150	1800	100	20	1.10	150	35	Fig.42	17	
SUR150-04NB	400	150	1700	100	20	1.30	150	50	Fig.42	17	
SUR150-06NB	600	150	1600	100	20	1.50	150	50	Fig.42	17	
SUR250-02NB	200	250	2600	150	20	1.10	250	35	Fig.42	17	
SUR250-04NB	400	250	2500	150	20	1.30	250	50	Fig.42	17	
SUR250-06NB	600	250	2400	150	20	1.50	250	50	Fig.42	17	
SUR300-02NB	200	300	3200	200	20	1.10	300	35	Fig.42	17	
SUR300-04NB	400	300	3100	200	20	1.30	300	50	Fig.42	17	
SUR300-06NB	600	300	3000	200	20	1.50	300	50	Fig.42	17	
SUR400-02NB	200	400	4900	300	20	1.10	400	35	Fig.42	17	
SUR400-04NB	400	400	4800	300	20	1.30	400	40	Fig.42	17	
SUR400-06NB	600	400	4700	300	20	1.50	400	50	Fig.42	17	
SRUD20020CT	200	2x100	1000	50	5	1.10	100	35	Fig.45	18	
SRUD20040CT	400	2x100	900	50	5	1.30	100	40	Fig.45	18	
SRUD20060CT	600	2x100	800	50	5	1.50	100	50	Fig.45	18	
SRUD20020CTD2	200	2x100	1000	50	5	1.10	100	35	Fig.44 (D2)	19	
SRUD20040CTD2	400	2x100	900	50	5	1.30	100	40	Fig.44 (D2)	19	
SRUD20060CTD2	600	2x100	800	50	5	1.50	100	50	Fig.44 (D2)	19	
SRUD30020CT	200	2x150	1400	100	6	1.10	150	35	Fig.45	18	
SRUD30040CT	400	2x150	1300	100	6	1.30	150	40	Fig.45	18	
SRUD30060CT	600	2x150	1200	100	6	1.50	150	50	Fig.45	18	
SRUD30020CTD3	200	2x150	1400	100	6	1.10	150	35	Fig.52 (D3)	19	
SRUD30040CTD3	400	2x150	1300	100	6	1.30	150	40	Fig.52 (D3)	19	
SRUD30060CTD3	600	2x150	1200	100	6	1.50	150	50	Fig.52 (D3)	19	
SRUD40020CT	200	2x200	1800	200	8	1.10	200	35	Fig.45	18	
SRUD40040CT	400	2x200	1700	200	8	1.30	200	40	Fig.45	18	
SRUD40060CT	600	2x200	1600	200	8	1.50	200	50	Fig.45	18	
SRUD40020CTD3	200	2x200	1800	200	8	1.10	200	35	Fig.52 (D3)	19	
SRUD40040CTD3	400	2x200	1700	200	8	1.30	200	40	Fig.52 (D3)	19	
SRUD40060CTD3	600	2x200	1600	200	8	1.50	200	50	Fig.52 (D3)	19	

内部电路 Circuits



Circuit 15 (SDF-B)



Circuit 16 (SDF-D4)



Circuit 17 (SUR-NB)



Circuit 18 (SRUD****CT)



Circuit 19 (SRUD****CTD2 / D3)

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	µA	µA	V	A	ns		
MUR820	200		8	100	20	1.5	1.5	8	50	TO-220AC	
MUR860	600		8	110	20	1.5	1.5	8	50	TO-220AC	
MUR8100	1000		8	110	20	1.5	1.5	8	50	TO-220AC	
MUR860S	600		8	110	20	1.5	1.5	8	50	TO-263	
MUR940	400		9	110	20	15	1.50	9	50	TO-220AC	
MUR960	600		9	110	20	1.5	1.5	9	50	TO-220AC	
MUR1020CT	200		10	55	5	0.1	1.25	10	30	TO-220AB	
MUR1040CT	400		10	55	10	0.25	1.5	10	35	TO-220AB	
MUR1520	200		15	110	50	3	1.7	15	50	TO-220AC	
MUR1560	600		15	110	50	3	1.7	15	50	TO-220AC	
MUR1560S	600		15	110	50	3	1.7	15	50	TO-263	
MUR1620CT	200		16	80	50		1.00	8	30	TO-220AB	
MUR1630PT	300		16	110	100	0.5	1.35	16	35	TO-247AD	
MUR1640CT	400		16	125	5	0.5	1.5	8	50	TO-220AB	
MUR1660CT	600		16	125	5	0.5	1.5	8	50	TO-220AB	
MUR1660	600		16	110	100	0.5	1.35	16	35	TO-220AC	
MUR2040CT	400		20	125	10	0.2	1.70	20	55	TO-220AB	
MUR2040CA	400		20	125	10	0.2	1.70	20	55	TO-220AB	
MUR2060CT	600		20	125	10	0.2	1.70	20	55	TO-220AB	
MUR2960S	600		29	300	100	7	1.4	29	50	TO-263	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	µA	µA	V	A	ns		
SUR20100CT	1000		10	75	250	4	2.1	12	50	TO-220AB	
SUR20100	1200		17	130	750	7	1.87	12	40	TO-220AC	
SUR20120	1200		17	130	750	7	1.87	12	40	TO-220AC	
SUR29120	1200		29	190	750	7	2.20	29	40	TO-220AC	
SUR120120	1200		120	600	3	20	1.55	70	40	TO-247AC	
SURB1610CT	100		8	100	20	1.5	1.3	8	35	TO-263	
SURB1620CT	200		8	100	20	1.5	1.3	8	35	TO-263	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	μA	μA	V	A	ns		
MUR3020	200		30	300	250	1	0.91	30	30	TO-247AC	
MUR3030	300		30	300	250	1	0.91	30	30	TO-247AC	
MUR3020PT	200		30	100	50	3	1.5	15	35	TO-247AD	
MUR3030PT	300		30	100	50	3	1.5	15	35	TO-247AD	
MUR3040PT	400		30	100	50	3	1.5	15	35	TO-247AD	
MUR3060PT	600		30	100	50	3	1.5	15	35	TO-247AD	
MUR3040	400		30	300	100	7	1.4	37	35	TO-247AC	
MUR3060	600		37	300	100	7	1.4	37	35	TO-247AC	
MUR3080	800		30	200	750	7	2	36	35	TO-247AC	
MUR30100	1000		30	200	750	7	2	36	35	TO-247AC	
MUR3080PT	800		30	75	250	4	2.1	15	50	TO-247AD	
MUR308100PT	1000		30	75	250	4	2.1	15	50	TO-247AD	
MUR30100PT	1000		30	75	250	4	2.1	15	50	TO-247AD	
MUR6020	200		69	600	50	11	0.88	60	35	TO-220AC	
MUR6020PT	200		60	325	200	5	0.85	30	35	TO-247AD	
MUR6030PT	300		60	325	200	5	0.85	30	35	TO-247AD	
MUR6030	300		60	550	200	14	1.5	70	35	TO-220AC	
MUR6040	400		60	325	200	14	1.5	70	35	TO-247AC	
MUR6060	600		60	325	200	14	1.5	70	35	TO-220AC	
MUR6040PT	400		60	300	100	7	1.4	37	35	TO-247AD	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	µA	µA	V	A	ns		
MUR6060PT	600		60	300	100	7	1.4	37	35	TO-247AD	
MUR6080	800		60	500	3000	14	1.8	60	35	TO-247AC	
MUR60100	1000		60	500	3000	14	1.8	60	35	TO-247AD	
MUR6080PT	800		60	200	750	7	2	36	35	TO-247AD	
MUR60100PT	1000		60	200	750	7	2	36	35	TO-247AD	
MUR8100	1000		12	75	250	4	2.1	12	50	TO-220AC	
MUR10100	1000		10	40	60	0.25	1.96	10	40	TO-220AC	
MUR10120	1200		10	40	60	0.25	1.96	10	40	TO-220AC	
MUR12060	600		126	600	3000	20	1.12	70	35	TO-247AC	
MUR15100	1000		15	75	250	4	2.1	15	50	TO-220AC	
MUR15120	1200		15	75	250	4	2.2	15	50	TO-220AC	
MUR20100	1000		17	130	750	7	1.87	12	40	TO-220AC	
MUR20120	1200		17	130	750	7	1.87	12	40	TO-220AC	
MUR30120	1200		30	200	750	7	2.2	30	40	TO-247AC	
MUR30120PT	1200		30	75	250	4	2.2	15	50	TO-247AD	
MUR60120	1200		52	500	2200	14	2.0	60	40	TO-247AC	
MUR60120PT	1200		60	200	750	7	2.2	30	40	TO-247AD	
MUR120120	1200		109	600	3000	20	1.55	70	40	TO-247AC	
MURB1610CT	100		16	80	5	0.1	1.1	8	30	TO-263	
MURB1620CT	200		16	80	5	0.1	1.1	8	30	TO-263	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	μA	μA	V	A	ns		
SUR2x30-04	400		30	300	100	7	1.4	30	35	SOT-227(IS OTOP)	
SUR2x30-06	600		30	300	100	7	1.4	30	35	SOT-227(IS OTOP)	
SUR2x30-08	800		30	200	750	7	2	30	35	SOT-227(IS OTOP)	
SUR2x30-10	1000		30	200	750	7	2	30	35	SOT-227(IS OTOP)	
SUR2x30-12	1200		28	200	750	7	2.2	30	40	SOT-227(IS OTOP)	
SUR2x60-02	200		71	950	50	11	0.88	60	35	SOT-227(IS OTOP)	
SUR2x60-04	400		60	550	200	14	1.5	60	35	SOT-227(IS OTOP)	
SUR2x60-06	600		60	50	200	14	1.5	60	35	SOT-227(IS OTOP)	
SUR2x60-08	800		60	500	3000	14	1.8	60	35	SOT-227(IS OTOP)	
SUR2x60-10	1000		60	500	3000	14	1.8	60	35	SOT-227(IS OTOP)	
SUR2x60-12	1200		52	450	2200	14	2.15	60	40	SOT-227(IS OTOP)	
SUR2x100-04	400		96	1200	3000	20	1.17	100	35	SOT-227(IS OTOP)	
SUR2x100-06	600		100	1200	3000	20	1.7	100	35	SOT-227(IS OTOP)	
SUR2x100-12	1200		91	900	3000	15	1.61	100	40	SOT-227(IS OTOP)	
MUR2x120-02	200		123	1200	1000	20	0.95	120	35	SOT-227(IS OTOP)	
SUR820	200		8	100	20	1.5	1.3	8	35	TO-220AC	
SUR860	600		8	100	20	1.5	1.3	8	35	TO-220AC	
SUR8100	1000		8	100	20	1.5	1.3	8	35	TO-220AC	
SUR860S	600		8	100	20	1.5	1.3	8	35	TO-263	
SUR1040CT	400		5	90	20	1.5	1.6	8	35	TO-220AB	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	µA	µA	V	A	ns		
SUR1060CT	600		5	90	20	1.5	1.6	8	35	TO-220AB	
SUR1520	200		15	100	50	3	1.5	16	35	TO-220AC	
SUR1560	600		15	100	50	3	1.5	16	35	TO-220AC	
SUR1560S	600		15	100	50	3	1.5	16	35	TO-263	
SUR1660CT	600		8	100	20	1.5	1.3	8	35	TO-220AB	
SUR2060CT	600		10	100	50	3	1.5	16	35	TO-220AB	
SUR2960	600		29	300	100	7	1.4	29	35	TO-220AC	
SUR2960S	600		29	300	100	7	1.4	29	35	TO-263	
SUR3020PT	200		15	100	50	3	1.5	16	35	TO-247AD	
SUR3030PT	300		15	100	50	3	1.5	16	35	TO-247AD	
SUR3040PT	400		15	100	50	3	1.5	16	35	TO-247AD	
SUR3060PT	600		15	100	50	3	1.5	16	35	TO-247AD	
SUR3020	200		30	300	100	7	1.4	37	35	TO-247AC	
SUR3030	300		30	300	100	7	1.4	37	35	TO-247AC	
SUR3040	400		30	300	100	7	1.4	37	35	TO-247AC	
SUR3060	600		30	300	100	7	1.4	37	35	TO-247AC	
SUR3080PT	800		15	75	250	4	2.2	15	50	TO-247AD	
SUR30100PT	1000		15	75	250	4	2.2	15	50	TO-247AD	
SUR30120PT	1200		15	75	250	4	2.2	15	50	TO-247AD	
SUR3080	800		30	200	750	7	2.2	30	40	TO-247AC	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	μA	μA	V	A	ns		
SUR30100	1000		30	200	750	7	2.2	30	40	TO-247AC	
SUR30120	1200		30	200	750	7	2.2	30	40	TO-247AC	
SUR6020	200		60	600	50	11	0.88	60	35	TO-247AC	
SUR6020PT	200		30	300	100	7	1.4	37	35	TO-247AD	
SUR6030PT	300		30	300	100	7	1.4	37	35	TO-247AD	
SUR6040PT	400		30	300	100	7	1.4	37	35	TO-247AD	
SUR6060PT	600		30	300	100	7	1.4	37	35	TO-247AD	
SUR6030	300		60	550	200	14	1.5	70	35	TO-247AC	
SUR6040	400		60	550	200	14	1.5	70	35	TO-247AC	
SUR6060	600		60	550	200	14	1.5	70	35	TO-247AC	
SUR6080PT	800		30	200	750	7	2.2	30	40	TO-247AD	
SUR60100PT	1000		30	200	750	7	2.2	30	40	TO-247AD	
SUR60120PT	1200		30	200	750	7	2.2	30	40	TO-247AD	
SUR6080	600		80	500	3000	14	1.8	60	35	TO-247AC	
SUR60100	1000		60	500	3000	14	1.8	60	35	TO-247AC	
SUR60120	1200		60	500	3000	14	1.8	60	35	TO-247AC	
SUR12060	600		120	600	3000	20	1.12	70	35	TO-247AC	
SUR15040SR	400		150	1500	50	4	1.1	150	35	TO-247SR	
SUR15100	1000		15	75	250	4	2.2	15	50	TO-220AC	
SUR15120	1200		15	1500	250	4	2.2	15	50	TO-220AC	

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	Datasheet
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	μA	μA	V	A	ns		
HUR2x30-30	300		30	300	250	1	0.96	30	30	SOT-227(IS OTOP)	PDF
HUR2x30-40	400		30	300	250	1	1.15	30	30	SOT-227(IS OTOP)	PDF
HUR2x30-60	600		30	250	250	1	1.30	30	35	SOT-227(IS OTOP)	PDF
HUR2x30-100	1000		30	200	250	1	1.96	30	40	SOT-227(IS OTOP)	PDF
HUR2x30-120	1200		30	200	250	1	1.96	30	40	SOT-227(IS OTOP)	PDF
HUR2x60-30	300		60	600	650	2.5	1.26	60	30	SOT-227(IS OTOP)	PDF
HUR2x60-40	400		60	600	650	2.5	1.26	60	30	SOT-227(IS OTOP)	PDF
HUR2x60-60	600		60	600	650	2.5	1.48	60	35	SOT-227(IS OTOP)	PDF
HUR2x60-100	1000		60	800	1000	4	1.70	60	40	SOT-227(IS OTOP)	PDF
HUR2x60-120	1200		60	800	1000	4	1.70	60	40	SOT-227(IS OTOP)	PDF
HUR2x100-40	400		100	1000	1000	4	1.24	100	30	SOT-227(IS OTOP)	PDF
HUR2x100-60	600		100	1000	1000	4	1.24	100	30	SOT-227(IS OTOP)	PDF
HUR820	200		8	80	50	0.2	0.94	8	25	TO-220AC	PDF
HUR820S	200		8	80	50	0.2	0.94	8	25	TO-263	PDF
HUR830	300		10	60	60	0.25	1.29	10	30	TO-220AC	PDF
HUR830S	300		10	60	60	0.25	1.29	10	30	TO-263	PDF
HUR1060	600		10	50	60	0.25	1.45	10	35	TO-220AC	PDF
HUR1520	200		15	140	100	0.5	1.21	15	30	TO-220AC	PDF
HUR1530	300		15	140	100	0.5	1.21	15	30	TO-220AC	PDF
HUR1540	400		15	140	100	0.5	1.21	15	30	TO-220AC	PDF

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	Datasheet
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	μA	μA	V	A	ns		
HUR1520S	200		15	140	100	0.5	1.21	15	30	TO-263	PDF
HUR1530S	300		15	140	100	0.5	1.21	15	30	TO-263	PDF
HUR1560	600		15	110	100	0.5	1.35	15	35	TO-220AC	PDF
HUR1620CT	200		8	80	50	0.2	0.94	8	25	TO-220AB	PDF
HUR1630T	300		8	60	60	0.25	1.29	10	30	TO-220AB	PDF
HUR2060CT	600		10	50	60	0.25	1.42	10	35	TO-220AB	PDF
HUR2960	600		30	250	250	1	1.26	30	35	TO-220AC	PDF
HUR3020CT	200		15	140	100	0.5	1.21	15	30	TO-220AB	PDF
HUR3030CT	300		15	140	100	0.4	1.21	15	30	TO-220AB	PDF
HUR3020CTS	200		15	14	100	0.5	1.21	15	30	TO-263	PDF
HUR3020PT	200		15	140	100	0.5	1.21	15	30	TO-247AD	PDF
HUR3030PT	300		15	140	100	0.5	1.21	15	30	TO-247AD	PDF
HUR3040PT	400		15	140	100	0.5	1.21	15	30	TO-247AD	PDF
HUR3030	300		30	300	250	1	0.91	30	30	TO-247AC	PDF
HUR3040	400		30	300	250	1	1.11	30	30	TO-247AC	PDF
HUR3060	600		30	250	250	1	1.25	30	35	TO-247AC	PDF
HUR3060PT	600		15	110	100	0.5	1.35	15	35	TO-247AD	PDF
HUR6030	300		60	700	650	2.5	1.25	60	30	TO-247AC	PDF
HUR6040	400		60	700	650	2.5	1.25	60	30	TO-247AC	PDF
HUR6030PT	300		30	300	250	1	0.91	30	30	TO-247AD	PDF

型号 TYPE	电气特性Electrical Characteristics									封装外形 Package Style	Datasheet
	VR=VRRM		IFAV	IFSM	IRRM 25°C	IRRM 125°C	VFMAX	IFM	Trr @RG1 CKT		
	V	°C	A	A	µA	µA	V	A	ns		
HUR6040PT	400		30	300	250	1	1.11	30	30	TO-247AD	PDF
HUR6060	600		60	600	650	2.5	1.39	60	35	TO-247AC	PDF
HUR6060PT	600		30	250	250	1	1.25	30	35	TO-247AD	PDF
HUR10100	1000		10	40	60	0.25	1.96	10	40	TO-220AC	PDF
HUR10120	1200		10	40	60	0.25	1.96	10	40	TO-220AC	PDF
HUR15100	1000		15	90	100	0.5	1.79	15	40	TO-220AC	PDF
HUR15120	1200		15	90	100	0.5	1.79	15	40	TO-220AC	PDF
HUR20100CT	1000		10	40	60	0.25	1.96	10	40	TO-220AB	PDF
HUR20120CT	1200		10	40	60	0.25	1.96	10	40	TO-220AB	PDF
HUR29100	1000		30	200	250	1	1.81	30	40	TO-220AC	PDF
HUR29120	1200		30	200	250	1	1.81	30	40	TO-220AC	PDF
HUR30100	1000		30	200	250	1	1.78	30	40	TO-247AC	PDF
HUR30120	1200		30	200	250	1	1.78	30	40	TO-247AC	PDF
HUR30100PT	1000		15	90	100	0.5	1.79	15	40	TO-247AD	PDF
HUR30120PT	1200		15	90	100	0.5	1.79	15	40	TO-247AD	PDF
HUR60100	1000		60	500	650	2.5	1.74	60	40	TO-247AC	PDF
HUR60120	1200		60	500	650	2.5	1.74	60	40	TO-247AC	PDF
HUR60100PT	1000		30	200	250	1	1.78	30	40	TO-247AD	PDF
HUR60120PT	1200		30	200	250	1	1.78	30	40	TO-247AD	PDF

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Россия +7(495)268-04-70

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://sirectifier.nt-rt.ru/> || sfx@nt-rt.ru